

Programming

The KESO KEK Programmer PPG V2 for both centralised and decentralised use.



The new KESO KEK Programmer PPG V2 for both centralised and decentralised programming.

The intelligent Two-in-One KESO KEK Programmer PPG V2 with two antennas and various interfaces.

KESO KEK Programmer PPG V2

The KESO KEK Programmer PPG V2 makes the programming of the KESO KEK family even more convenient as it enables all KESO-Media and electronics to be programmed centrally and de-centrally.

The authorisations of up to 8,000 KEK access media plus all time-windows, data and all parameters are transferred into the electronics. When programming the data it can be selected at the same time whether the event memory should be read. The battery status can be read and reset on-site. Also the firmware can update all electronics which have a serial interface or KAPI* bus

Benefits

- Combines the options from KESO KEK
- USB Programmer and KESO KEK Programmer PPG V1 in one device
- Offline-Programming, reading of cylinders, readers, fittings and keys
- Automatic identification of the electronics on download
- Manageable, robust, compact
- Very easy to use via clear touch-screen
- Multilingual (9 languages)

Requirements:

- Processor: Pentium III or higher
- Working memory at least 128 MB
- Memory requirement: at least 150 MB for the KESO K4 Software (without databases)

Technical data

- Dimensions: 140x66x23 mm
- Weight: 165 g
- Power supply: Lithium-ion polymer battery
- Programmable: KESO KEK Family
- Communication: serial, KAPI* or RF (key adapter)
- Set: Complete with power supply, all adaptors, operating instructions (E, F, G, I) and standard cables

Options

Docking-Station, leather case, special cable

Article number

Standard: K.536

* KESO Advanced Programming Interface



KEKnet compatible

- Drives: CD-ROM
- Operating system: Microsoft® Windows 2000 (Service Pack 4 or higher), Microsoft® Windows XP (from Service Pack 1 or higher), Microsoft® Windows Vista™
- Graphics card: at least 800x600 (SVGA) with 256 colours
- Software: KESO K4 Software V4.0.40 or higher
- Interfaces: USB 2.0

1. Practical: Keys are placed in the antenna for programming.

2. On the rear side: Printed positioning help for the KESO Tag and KESO Keycard.



KESO AG
Security Systems
Untere Schwandenstr. 22
CH-8805 Richterswil

Phone +41 44 787 34 34
Fax +41 44 787 35 35
info@keso.com
www.keso.com